

ROOF ACCESS HATCH



- Finest quality and workmanship
- Nationwide availability
- Stock readily available
- Available in many sizes
- Highly visible safety caution striping
- Durable recoatable gray primer finish (standard)

Standard Sizes

(Special sizes available upon request)

SIZE	FRAME ID	FRAME OD	ROOF OPENING	SHIPPING WT lbs/kg.
24 x 24	24 x 24	31 x 31	24 x 24	115 / 52.1 kg
24 x 30	24 x 30	31 x 37	24 x 30	125 / 56.7 kg
24 x 36	24 x 36	31 x 43	24 x 36	135 / 61.2 kg
30 x 36	30 x 36	37 x 43	30 x 36	155 / 70.3 kg
30 x 54	30 x 54	37 x 61	30 x 54	225 / 102 kg
30 x 96	30 x 96	37 x 103	30 x 96	335 / 152 kg
36 x 36	36 x 36	43 x 43	36 x 36	200 / 90.7 kg
48 x 48	48 x 48	55 x 55	48 x 48	430 / 195 kg

FOR SPECIAL SIZES CALL ELMDOR/STONEMAN (800)-591-9181

17451 Hurley St. • P.O. Box 3527, City of Industry, Ca 91744-0527

(800) 591-9181 • (626) 968-8699 • Fax (626) 333-4109

www.elmdorstoneman.com • e-mail: info@elmdorstoneman.com



PRODUCT SPECIFICATIONS

Curb Construction:


Curb shall be 14 gage (G 90) galvanized steel with durable recoatable gray primer finish standard. Curb shall be 12" (304mm) in height with a 4" (101mm) fiber board insulation, and mounting holes for roof attachment. Curb shall have integral cap flashing of the same material and thickness as the curb. Curb and cap flashing shall be fully welded at the corners for a watertight construction. Hinges are two-piece formed steel, with a non-removable heavy-duty pivot pin.

Cover:

Cover shall be 14 gage (G 90) galvanized steel, with radiused corners for safety, and shall be fully welded at the corners for watertight construction. The cover liner shall be 22 gage. The cover shall be insulated with a 1" (25.4mm) thick fiberglass insulation, and reinforced as required to support a 40#/ft square live load. An extruded rubber gasket, mechanically fastened to the inside of the lid shall cause the hatch lid to seal.

Hardware:

Hardware shall include interior handle, with a positive, one-point locking mechanism, exterior handle, and provisions for a padlock, both inside and out. Pre-lubricated compression springs, encased in zinc-plated telescopic tubes, for smooth and controlled door operation at any position. An automatic, hold-open arm, with vinyl grip, shall be standard. All hardware shall be corrosion resistant, and all fasteners shall be of a self-locking type.



17451 Hurley St. • P.O. Box 3527, City of Industry, Ca 91744-0527

(800) 591-9181 • (626) 968-8699 • Fax (626) 333-4109

www.elmdorstoneman.com • e-mail: info@elmdorstoneman.com

L #1000895